



Safety System

- ▶ Anti-fall locks Limit
- ▶ Emergency stop button
- ▶ Lock down button
- ▶ Limit switches
- ▶ Photocell sensor

Application Scenarios

Vehicle Model	Sedan, Small SUV
Foundation	C25-C30; thickness: ≥ 200mm
Ceiling Height	≥ 149" (Sedan+SUV)/169" (2 SUVs)
Buildings	Private Garage; Residential Community; Shopping Mall; 4S Shop; Car Dealership
Environment	Indoor/Outdoor (Outdoor protection devices available)

Features

- One Hydraulic Lifting Chains Direct
- 70" Parking Height
- 100% Laser Cutting Process for All Parts and the Whole Structure
- Preassembled Parts for Easy Installation
- Effortless Disassembly and Relocation
- Safety Key Switch Controller
- Hydraulic Overload Protection
- Anti-Skid Ramp and Platform
- Anti-Rust Smooth Powder Coating Finishing
- Enhanced Anti-Corrosion Galvanized
- Waving Plates
- Tire Protection Plates
- IP65 Electrical Devices Available for Outdoor Use
- 5 year warranty parts, 1 year labor
- Customizable Colors
- The front and rear interchangeable parking ramps allow users to get on and off the car
- Saving-space single column design, better parking experience

Parameters

Model	SAL-1P
Lifting Capacity	44091b
Vehicle Height	70.87"
Vehicle Width	≤82.68"
Vehicle Length	196"
Control Box	Integrated Modules for Simple Wiring
Power Unit	2.2 KW Hydraulic
Electrical Requirements	120v, 60Hz 1 Phase
Control Power	24V
Parking Time	45-55 Seconds

*Most parameters can be customized based on your requirements.

