

Two Post Car Parking Lift  
**SAL-2PTW**



### Safety System



- ▶ Full range anti-fall locks
- ▶ Emergency stop button
- ▶ Lock down button
- ▶ Limit switches
- ▶ Photocell sensor

#### APPLICATION SCENARIOS

Vehicle Model	Sedan, Regular SUV
Foundation	C25-C30, thickness > 6 Inches
Ceiling Height	153 1/2 Inches (Sedan+SUV) / 169 1/4 Inches (2 SUVs)
Buildings	Residential or Storage
Environment	Indoor/Outdoor (Outdoor protection devices available)

### Features

- Double hydraulic lifting cylinder direct drive
- Multiple parking heights
- 100% Laser cutting process for all parts and the whole structure • Preassembled parts for easy installation
- Effortless disassembly and relocation
- Safety key switch controller
- Hydraulic overload protection
- Anti-skid ramp and platform
- Anti-rust smooth powder coating finishing • Enhanced anti-corrosion galvanized waving plates
- Tire protection plates
- IP65 electrical devices available for outdoor use
- 5-year warranty (on parts, 1-year warranty on labor
- Customizable colors
- Posts can be shared for multiple parallel lifts



PARAMETERS	
Model	SAL-2PTW
Lifting Capacity	7,055 lbs
Vehicle Height	Up to 80"
Vehicle Width	Up to 94"
Vehicle Length	< 197"
Control Box	Integrated modules for simple wiring
Power Unit	3.0 kW Hydraulic
Electrical Requirements	Residential 220V, 1 phase Commercial 250V, 3 phase
Parking Time	45-55 seconds
*Most parameters can be customized based on your requirements.	

