



**APPLICATION SCENARIOS**

Vehicle Model	Sedan, regular SUV
Foundation	Slab thickness recommended 9.0"
Ceiling Height	216 1/2 Inches
Buildings	Residential or Storage
Environment	Indoor/Outdoor (Outdoor protection devices available)


**Features**

Single hydraulic lifting cylinder direct drive  
Multiple parking heights  
100% Laser cutting process for all parts and the whole structure  
Preassembled parts for easy installation and relocation  
Safety key switch controller

Anti-skid ramp and platform  
Anti-rust smooth powder coating finish  
Customizable colors  
Lock release: Electrical  
5-year warranty on parts, 1-year warranty on labor  
Three vehicles parked at the same time

**Safety System**

Full range anti-fall locks  
Limit switches  
Emergency stop button  
Anti-loosening locks



PARAMETERS	
Model	SAL-4P3
Lifting Capacity	4,409 lbs (upper); 5,512 lbs (middle)
Vehicle Height	71"
Vehicle Width	84"
Vehicle Length	< 196 3/4"
Control Box	Integrated modules for simple wiring
Power Unit	3.0 kW Hydraulic
Electrical Requirements	208-240V, 3 phase
Parking Time	55 seconds

\*Most parameters can be customized based on your requirements.

