



Safety System

- ▶ Anti-fall locks Limit
- ▶ Limit switches
- ▶ Emergency stop button
- ▶ Photocell sensor
- ▶ Lock down button

Application Scenarios

Vehicle Model	Sedan, Small SUV
Foundation	C25-C30; thickness: ≥ 200mm
Ceiling Height	≥ 149" (Sedan+SUV)/169" (2 SUVs)
Buildings	Private Garage; Residential Community; Shopping Mall; 4S Shop; Car Dealership
Environment	Indoor/Outdoor (Outdoor protection devices available)

Features

- One Hydraulic Lifting Chains Direct 70" Parking Height 100%
- 100% Laser cutting process for all parts and the whole structure
- Preassembled parts for easy installation
- Effortless disassembly and relocation
- Safety key switch controller
- Hydraulic overload protection
- Anti-skid ramp and platform
- Anti-rust smooth powder coating finishing
- Enhanced anti-corrosion galvanized waving plates
- 5-year warranty on parts, 1-year warranty on labor
- Posts can be shared for multiple parallel lifts
- Tire Protection Plates IP65
- Electrical Devices Available for Outdoor Use
- The front and rear interchangeable parking ramps allow users to get on and off the car
- Saving-space single column design

Parameters

Model	SAL-1P
Lifting Capacity	4409lb
Vehicle Height	70.87"
Vehicle Width	≤82.68"
Vehicle Length	196"
Control Box	Integrated Modules for Simple Wiring
Power Unit	2.2 KW Hydraulic
Electrical Requirements	120v, 60Hz 1 Phase
Control Power	24V
Parking Time	45-55 Seconds
*Most parameters can be customized based on your requirements.	

