



Safety System


- ▶ Full range anti-fall locks
- ▶ Emergency stop button
- ▶ Lock down button
- ▶ Limit switches
- ▶ Photocell sensor

APPLICATION SCENARIOS

Vehicle Model	Sedan, Regular SUV
Foundation	C25-C30, thickness > minimum 4 Inches, suggested 6 Inches
Ceiling Height	153 1/2 Inches (Sedan+SUV) / 169 1/4 Inches (2 SUVs)
Buildings	Residential or Storage
Environment	Indoor/Outdoor (Outdoor protection devices available)

Features

- Single hydraulic lifting cylinder direct drive
- Multiple parking heights
- Faster lifting speed than other two post lifts
- 100% Laser cutting process for all parts and the whole structure
- Preassembled parts for easy installation
- Effortless disassembly and relocation
- Safety key switch controller
- Hydraulic overload protection
- Anti-skid ramp and platform
- Anti-rust smooth powder coating finishing
- Enhanced anti-corrosion galvanized waving plates
- 5-year warranty on parts, 1-year warranty on labor
- Posts can be shared for multiple parallel lifts



PARAMETERS	
Model	SAL-2PSW
Lifting Capacity	7,055 lbs
Vehicle Height	Up to 80"
Vehicle Width	Up to 87 1/2"
Vehicle Length	< 197"
Control Box	Integrated modules for simple wiring
Power Unit	2.2 kW Hydraulic
Electrical Requirements	120V, 1 phase
Parking Time	45-55 seconds

***Most parameters can be customized based on your requirements.**

