

## Eight Post Triple Car Parking Lift

### SAL-8P3

## Safety System

- Full Range Anti-Fall Locks
- Limit Switches
- Emergency Stop Button
- Anti-Loosening Locks

## Features

- Independent hydraulic system
- Multiple Parking Heights
- 100% Laser Cutting Process for All Parts and the Whole Structure
- Preassembled Parts for Easy Installation and Relocation
- Press Button Operation Box
- Hydraulic Overload Protection
- Anti-Skid Ramp and Platform
- Anti-Rust Smooth Powder Coating Finishing
- Enhanced Anti-Corrosion Galvanized Waving Plates
- Optional: Middle Cover Plate, Oil Drip Tray and Tire Protection Plate
- Customizable Colors
- Suitable for Auto Repair Shops
- Lock Release: Electrical
- Flexibility: Easy to Be Separated into Two Individual Lifts
- 12-Month Warranty (Extended Warranty Available)

## Parameters

| Model                   | SAL-8P3                                            |
|-------------------------|----------------------------------------------------|
| Lifting Capacity        | 2700 KG(Upper); 3600 KG(Middle)                    |
| Vehicle Height          | 1,550-1,750 MM                                     |
| Vehicle Width           | ≤ 1,850 MM                                         |
| Vehicle Length          | 5,100 MM                                           |
| Control Box             | Integrated Modules for Simple Wiring               |
| Power Unit              | 2.2 KW Hydraulic                                   |
| Electrical Requirements | Voltage: Customizable; 1-phase or 3-phase; 50/60Hz |
| Control Power           | 24 V                                               |
| Parking Time            | 50 Seconds                                         |

\*Most parameters can be customized based on your requirements.



## Application Scenarios

|                |                                                                        |
|----------------|------------------------------------------------------------------------|
| Vehicle Model  | Sedan, SUV, regular Pick-up Truck                                      |
| Foundation     | C25-C30; THICKNESS: ≥ 12"                                              |
| Ceiling Height | 220 1/2"                                                               |
| Buildings      | Garage; Parking Lot; Car Repairing; Car Dealer; 4S Shop; Shopping Mall |
| Environment    | Indoor/Outdoor (Outdoor protection devices available)                  |

